

Model Range for INDEX Multi Spindle Automatic Lathes MS 18 – MS 52

MS 18	MS 32	MS 52
Axial Driven Head up to 6'000 min-1 Page 01	Axial Driven Head up to 6'000 min-1 Page 31	Axial Driven Head up to 6'000 min-1 Page 61
Axial Driven Head Offset up to 9'000 min-1 Page 02	Axial Driven Head Offset up to 9'000 min-1 Page 32	Axial Driven Head Offset up to 9'000 min-1 Page 62
Axial Driven Head Offset up to 12'000 min-1 Page 03	Axial Driven Head Offset up to 12'000 min-1 Page 33	Axial Driven Head Offset up to 12'000 min-1 Page 63
Angle Head 90° up to 6'000 min-1 Page 04	Angle Head 90° up to 6'000 min-1 Page 34	Angle Head 90° up to 6'000 min-1 Page 64
Angle Head 90° up to 9'000 min-1 Page 05	Angle Head 90° up to 9'000 min-1 Page 35	Angle Head 90° up to 9'000 min-1 Page 65
Angle Head 90° up to 12'000 min-1 Page 06	Angle Head 90° up to 12'000 min-1 Page 36	Angle Head 90° up to 12'000 min-1 Page 66
	2-spindle Angle Head 90° up to 6'000 min-1 Page 37	2-spindle Angle Head 90° up to 6'000 min-1 Page 67
	2-spindle Angle Head 90° up to 9'000 min-1 Page 38	2-spindle Angle Head 90° up to 9'000 min-1 Page 68
	2-spindle Angle Head 90° up to 12'000 min-1 Page 39	2-spindle Angle Head 90° up to 12'000 min-1 Page 69

Excerpt of available standard and special heads



INDEX multi spindle MS 52

One of our engineering goals for axial and radial holders was to reduce set-up time for assembly and disassembly of different driven holders. Thanks to the close cooperation with the INDEX multi spindle department, we were successful in reducing the cycle time by implementing our mono block and clever adjustment system. Together with the short set-up time, great reliability and modular style future applications can be utilized with these SU-matic products.



2-spindle unit up to 12,000 RPM



SU-matic heads in practice